

3

secondary space in the interior lavatory space in an area forward of an aft-most portion of the forward wall portion. The secondary space can provide an amenity stowage space inside the lavatory stall unit in the area forward of an aft-most portion of the forward wall portion, and can include design elements providing visual space inside the lavatory in the area forward of an aft-most portion of the forward wall portion.

In another presently preferred aspect, the present invention provides for an assembly of an aircraft enclosure unit and an aircraft cabin structure for an aircraft cabin, the assembly in combination including an aircraft cabin structure having an exterior aft surface having a shape that is substantially not flat in a vertical plane, and an aircraft enclosure unit including at least one wall having a forward wall portion. The one or more walls define an interior enclosure space, the forward wall portion is disposed immediately aft of and adjacent to the aircraft cabin structure, and the forward wall portion is shaped to substantially conform to the shape of the exterior aft surface of the aircraft cabin structure. In another presently preferred aspect, the aircraft cabin structure is a passenger seat installed immediately forward of the aircraft enclosure unit. In another presently preferred aspect, the forward wall portion is configured to accept loads from the aircraft passenger seat. In another presently preferred aspect, the forward wall portion includes a forward projection configured to project over an aft portion of the adjacent passenger seat immediately forward of the aircraft enclosure unit.

In another presently preferred aspect, the aircraft enclosure unit is a lavatory stall, and the one or more walls define an interior lavatory space. In another presently preferred aspect, the forward wall portion defines a secondary space in the interior lavatory space in an area forward of an aft-most portion of the forward wall portion.

In another presently preferred aspect, the present invention provides for an assembly of an aircraft lavatory unit and an aircraft cabin structure for an aircraft cabin, in which the assembly in combination includes an aircraft cabin structure having an exterior aft surface having a shape that is substantially not flat in a vertical plane, and an aircraft lavatory stall unit including one or more walls having a forward wall portion. In another presently preferred aspect, the one or more walls define an interior lavatory space, the forward wall portion is disposed immediately aft of and adjacent to the aircraft cabin structure, and the forward wall portion is shaped to substantially conform to the shape of the exterior aft surface of the aircraft cabin structure. In another presently preferred aspect, the aircraft cabin structure is a passenger seat installed immediately forward of the aircraft lavatory stall unit, and wherein the forward wall portion of the aircraft lavatory stall unit is configured to accept loads from the passenger seat. In another presently preferred aspect, the forward wall portion includes a forward projection configured to project over an aft portion of the adjacent passenger seat immediately forward of the aircraft lavatory stall unit. In another presently preferred aspect, the forward wall portion defines a secondary space in the interior lavatory space in an area forward of an aft-most portion of the forward wall portion.

These and other aspects and advantages of the invention will become apparent from the following detailed description and the accompanying drawings, which illustrate by way of example the features of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a prior art installation of a lavatory immediately aft of and adjacent to an aircraft passenger seat.

4

FIG. 2 is a schematic diagram of an installation of a lavatory according to the present invention immediately aft of and adjacent to or abutting an aircraft cabin passenger seat.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the drawings, which are provided by way of example, and not by way of limitation, the present invention provides for an enclosure 10, such as a lavatory for a cabin 12 of an aircraft (not shown), although the enclosure may also be an aircraft closet, or an aircraft galley, or similar enclosed or structurally defined spaces, for example. As is illustrated in FIG. 2, the cabin includes a structure 14, and the enclosure may be taller than the cabin structure. The cabin structure can be a passenger seat 16, for example, installed immediately forward of the enclosure and having an aft portion 18 with an exterior aft surface 20 that is substantially not flat in a vertical plane 22. The lavatory includes a lavatory stall unit 24 having one or more walls 26 having a forward wall portion 28. The one or more walls define an interior lavatory space 30, and the forward wall portion is configured to be disposed immediately aft of and adjacent to or abutting the exterior aft surface of the aircraft cabin structure. The forward wall portion has a shape that is substantially not flat in the vertical plane, and preferably is shaped to include a recess 34 such that the forward wall portion substantially conforms to the shape of the exterior aft surface of the aircraft cabin structure. In a presently preferred aspect, the forward wall portion of the lavatory stall unit is configured to accept loads from the passenger seat. As shown in FIG. 2, the forward wall portion 28 can be configured to provide a lower recess 100 formed between the forward wall portion 28 and the cabin deck 102. As also shown in FIG. 2, the lower recess 100 can be configured to receive at least a portion of an aft-extending seat support 17 therein. As can be seen by comparing FIG. 1 and FIG. 2, the recess 34 and the lower recess 100 combine to permit the passenger seat 16 to be positioned farther aft in the cabin than would be possible if the lavatory enclosure 10 included a conventional flat and vertical forward wall without recesses like that shown in FIG. 1, or included a forward wall that did not include both recesses 34, 100.

In another presently preferred aspect, the forward wall portion defines a secondary space 36 in the interior lavatory space in an area 38 forward of an aft-most portion 40 of the forward wall portion, and the forward wall portion includes a forward projection 42 configured to project over the aft portion of the adjacent passenger seat back 44 immediately forward of the lavatory stall unit. The secondary space can include an amenity stowage space 46 inside the lavatory stall unit in the area forward of the aft-most portion of the forward wall portion, and the secondary space can include design elements providing visual space, such as a visual perception of space, inside the lavatory in the area forward of an aft-most portion of the forward wall portion.

It will be apparent from the foregoing that while particular forms of the invention have been illustrated and described, various modifications can be made without departing from the spirit and scope of the invention. Accordingly, it is not intended that the invention be limited, except as by the appended claims.

We claim:

1. An aircraft lavatory for a cabin of an aircraft of a type that includes a forward-facing passenger seat that includes an upwardly and aftwardly inclined seat back and an aft-extending seat support disposed below the seat back, the lavatory comprising: